
ANNOUNCEMENT APPLIANCE AA-4860

USER GUIDE

Introduction

The *Announcement Appliance* Model AA-4860 is a 'no-frills' automatic telephone voice announcer. Importance has been placed on good quality voice reproduction rather than supplementary facilities. Also, no external power supply is required for the system to operate.

You can personally record your voice announcement from any telephone and the announcement can run for up to two minutes (longer to order).

Applications for this device include recorded information services, automatic call distribution (ACD) announcements and for Operator overflow.

Connection

The *Announcement Appliance* is simply connected to any two wire analogue (ring in/loop out) telephone line using the line cord provided. No other connections are required.

Note: When the *Announcement Appliance* is playing or recording, the 'Record/Play' LED indicator illuminates.

Instructions

To Record Your Announcement

1. Dial up the *Announcement Appliance* and wait for it to answer.
2. Press # during the current announcement so that it stops playing.
3. Enter the preset four digit PIN (the default PIN is 1234).
4. Listen for the 'beep' tone and then start dictating your new announcement into the telephone.
5. To finish recording, press #. The new announcement will be replayed to you.

Specifications

Enclosure	Injection molded ABS.
Dimensions	50 mm x 110 mm x 80 mm.
Operating Temperature Range	-10 → +70 ° C.
Voice Recording /Playback	
Input Sample Rate	8 kHz.
Upper pass band	3.4 kHz.
Message retention	100 years.
Record Cycles	100, 000.
Messages length	Up to 120 seconds.
Output level	-13.5 → 0 dBm adjustable.
Frequency range	500 Hz → 3.4 kHz.
Line Interface	Two wire analogue ring in, loop out.
Connector	RJ12.
Displays	Record/Play LED indicator (green).
NZ Telepermit	PTC 212/92/005.
ACA Supplier's Code Number	N468.
Warranty	Two years.

design2000

Est. 1968

Telephone: +613 9758 5933
Web Site: www.design2000.com.au