

---

## DIGITAL PRESSURE GAUGE MODEL PG-4288

The Digital Pressure Gauge, Model PG-4288, is designed to measure and monitor pressurized cable. It is a portable instrument used by external plant staff involved in the installation and maintenance of the pressurized cable network. It is currently the only serial/item (421/46) certified by Telstra for the purpose of accurate cable pressure measurements and identifying air leakage.

### Specifications

Reading Unit:	kPa
Range:	0 → 150 kPa
Accuracy:	± 0.5 kPa, 0 → 50 °C
Resolution:	0.1 kPa
Reading response time:	Within 3 seconds of being commanded by operator
Battery life:	30 hours continuous with 9V alkaline transistor battery
Air chuck:	Schrader Model No. 6662 side entry type
Hose Length:	1 m
Carry Handle:	Styrene-butadiene rubber
Protective Holster:	Nitrile rubber
Dimensions:	H 150mm x W 80 mm x D 50 mm
Serial/Item:	421/46



---

MADE IN AUSTRALIA

**design2000**

Est. 1968

[www.design2000.com.au](http://www.design2000.com.au)

**DESIGN TWO THOUSAND PTY LTD**

TELEPHONE: 03 9758 5933  
E-MAIL: [gen@design2000.com.au](mailto:gen@design2000.com.au)

FACSIMILE: 03 9758 5560  
WEB SITE: [www.design2000.com.au](http://www.design2000.com.au)



N468



For

**Telstra**